




# SANTONI™

# PULSAR

DOUBLE JERSEY INTERLOCK MACHINE

双面棉毛机



Excellent for Interlock fabrics  
with/without elastane  
带或不带弹力纱的极佳棉毛织物

High precision design for fine gauge  
(up to E44)  
高精度的细针设计（高达44机号）

Higher productivity and flexibility  
更高的生产效率和更多的灵活性

## PULSAR 简介



- 用于生产棉毛和8锁结构织物的双面针织机。
- 机器配置针筒4跑道，针盘2跑道结构。
- 每英寸2.8路的多功能机。在筒径和每英寸路数之间的最佳组合，产生了高效率生产与高质量产品。
- 独立三角座由特殊铝合金（Ergal）制成，具有超强散热功能。
- 牵拉装置的自动定位使落布卷更加快捷。
- 由圣东尼公司开发设计的织针与三角轮廓，精确而稳定地保证织针的运行。
- 通过精细螺丝调节三角位置。
- 可以选择圆筒机架或开幅机架（标准款和大卷装款）。
- 只需简单操作即可将开幅机架换为圆筒机架。
- 非常紧凑的开幅机架，便于进入编织区域。

## PULSAR BRIEF



- Double jersey machine for the production of interlock and 8 lock structured fabrics.
- Machine can receive up to 4 cam tracks on cylinder and 2 on the dial.
- Very versatile machine with 2.8 feeders per diametrical inch.
- The perfect relation between diameter and number of feeds per inch aims at getting the best fabric quality together with high productivity.
- Individual cam shells made by special aluminum alloy (ergal) having a great heat dissipation property.
- Automatic positioning of the fabric take down or quick removal of fabric roll.
- Design of the needles and cams profile through a formula developed by Santoni assuring a precise and stable movement of the needles.
- Very precise cam adjustment by micrometrical screws.
- Available with tubular as well as Open width frame (standard and industrial).
- Very compact open frame for an easy access to the knitting head.

# PULSAR



# SANTONI™



筒径	26	28	30	32	34	36	38	40	Diameter	26	28	30	32	34	36	38	40
针距	18 - 44								Gauge	18 - 44							
路数	72	78	84	88	94	100	106	112	Number of feeds	72	78	84	88	94	100	106	112
最高转速	37	34	32	30	28	27	25	24	Maximum Speed (RPM)	37	34	32	30	28	27	25	24

		布卷/毫米	机架尺寸/毫米			Fabric roll/MM	Fabric size/MM
机架	标准圆筒机架	500		Frame	Tubular standard	500	
	大卷装圆筒机架	780	+ 500		Tubular industrial	780	+ 500
	大卷装圆筒机架	1080	+ 800		Tubular industrial	1080	+ 800
	标准开幅机架	380			Open width standard	380	
	大卷装开幅机架	600	+ 300		Open width industrial	600	+ 300

标准配置	<ul style="list-style-type: none"> <li>- 侧纱架</li> <li>- 积极送纱装置</li> <li>- 独立的三角座, 可安装4跑道三角, 针盘2跑道三角</li> <li>- 上翻式黑锆陶瓷导纱嘴</li> <li>- 细微线长调节</li> <li>- Uniwave 机头吹尘</li> <li>- 自动加油系统</li> <li>- 电动马达驱动 (变频器)</li> <li>- LFA线长测量装置</li> <li>- 电子探针器</li> <li>- 马达控制剪裁开幅刀和斜向导布辊</li> </ul>	Standard Equipment	<ul style="list-style-type: none"> <li>- Aluminum side creel</li> <li>- Positive feeding units</li> <li>- Individual cam shells prepared to receive up to 4 cam tracks on cylinder and 2 on dial</li> <li>- Flip-up Zirconium yarn carrier</li> <li>- Micrometrical stitch adjustment</li> <li>- Uniwave flutter blowers on knitting head</li> <li>- Automatic oiling system</li> <li>- Electronic motor drive(inverter)</li> <li>- LFA-Yarn input measuring device</li> <li>- Electronic needles detector</li> <li>- Motorized slitting and fabric opening system (Open width)</li> </ul>
------	---	--------------------	--

选配件	<ul style="list-style-type: none"> <li>- 裸氨纶送纱器</li> <li>- 开幅机架 (26" - 32", 220厘米; 34"以上, 245厘米)</li> <li>- 摆布装置 (圆筒机架)</li> <li>- 大卷装机架 (圆筒和开幅)</li> </ul>	Optional	<ul style="list-style-type: none"> <li>- Lycra feeding units</li> <li>- Open width frame (26" - 32", 220cm - above 34",245 cm)</li> <li>- Lapping device system(tubular frame)</li> <li>- Industrial frame(both tubular and open width)</li> </ul>
-----	---	----------	--

产品应用	内衣, 运动衣, 泳衣, 医疗用布, 工艺用布	Application area	Underwear, Sportswear, Swimwear, Medical Textiles, Technical Textiles
------	-------------------------	------------------	---



Disclaimer: All features in the brochure are for information only and subject to change without any prior notice. For a complete list of configuration, please contact Santoni Shanghai sales network.

声明: 宣传单中的所有信息仅作参考, 圣东尼公司有权先行修改。请联系圣东尼 (上海) 销售部查询完整配件清单。

2019 V01

SANTONI (SHANGHAI) KNITTING MACHINERY CO.,LTD

Add: No.111, East Shanfu Road, Jinshan, Shanghai 201508, China

Tel: +8621-57240777 Fax: +8621- 3721 2624 Website: www.santoni.cn

圣东尼 (上海) 针织机器有限公司

地址: 上海市金山区山富东路111号 邮编: 201508

总机: +8621-57240777 传真: +8621-3721 2624 网站: www.santoni.cn