

SS-605X



☆ SINCE 1980



CHARACTERISTIC

◆ Footie socks

◆ 6 colors + 1 ground

◆ Selected terry

◆ High-performance

◎ Knit scales :

Single or double welt, full & half(top and bottom) & selected terry(terry-designed), heel & toe in different sizes and types(Y heel, big and small heel etc), minimum 2 colors in heel & toe, 3D effects(reversed heel & toe) and footie socks, mock ribs, tuck, mesh, 3 color jacquard patterns, two-tone elastic, left & right, full elastic and tubular fabric etc.



Santoni (Shanghai) Knitting Machinery Co., Ltd.

DISCLAIMER The technical specification on this brochure is for the guidance purpose only. Santoni (Shanghai) Knitting Machinery Co., Ltd. reserves all the right to amend and interpret the details of technical specifications on this brochure.



Company website

SS-605X

The detailed specification of product

1. Textile possibilities

- ◆ Embroidery pattern max 5 or 6 colors + 1 ground in a single cycle
- ◆ Embroidery pattern max 4 or 5 colors + 1 ground + elastic floating in a single cycle
- ◆ Embroidery pattern max 4 or 5 colors + 1 mesh ground in a single cycle
- ◆ 2 color jacquard patterns + embroidery pattern max 4 or 5 colors in a single cycle
- ◆ 2 color jacquard patterns + elastic floating in a single cycle
- ◆ 3 color jacquard patterns in a single cycle
- ◆ The total embroidery pattern max 13-17 colors can be added in a single sock

2. Product features

- ◆ 8 pcs of yarn finger on the main feeder
- ◆ 1-2 pcs of yarn finger on the elastic feeder
- ◆ 13-17 pcs of yarn finger on the color feeder
- ◆ 1-3 pcs of yarn finger on the assistant feeder
- ◆ The total 23-30 pcs of yarn finger

3. Technical features

- ◆ Equipped with "made in Korea" solenoid valves
- ◆ Equipped with "made by Soosan" 6-7 magnetic actuators with 16 flaps for jack selection
- ◆ Equipped with "made in Japan" 1 ceramic actuator with 6 flaps for sinker selection
- ◆ Density adjustment by step motors
- ◆ Possible to store several articles in CPU memory
- ◆ Possible to run a sequence of up to 4 different articles
- ◆ Possible to modify the programs and the parameters on machine computer
- ◆ Programs are loaded through USB
- ◆ UPS power backup system
- ◆ Automatic lubrication

4. Available options

- ◆ Device for A type of advanced center cam (Advantage: terry footie)
- ◆ Device for second elastic feeder
- ◆ Device for extra embroidery pattern color
- ◆ Device for one more movement of main finger
- ◆ Device for one more extra color feeder with actuator (1 ground + 6 colors) 7F
- ◆ Device for anti-twist
- ◆ Install step motor for controlling position of sinker cap
- ◆ Install step motor for controlling speed of ring cutter
- ◆ IRO yarn feeder
- ◆ BTSR yarn flow sensor
- ◆ Advanced mechanical yarn flow sensor
- ◆ Socks detector
- ◆ Advanced yarn creel
- ◆ Suction fan

5. Technical data

Model	Cylinder Diameter (")	Function	Gauge	Needle Count (N)	Max Running Speed (RPM)	Power Required(kw)		
						Drive Motor	Blow Motor	Control Box
SS-605XU	3 ³ / ₄ "	plain / terry (selected terry)	36-48	72-198	300 (Plain)	1-1.1	≥ 1.1	0.80
SS-605XT	4"				250 (Terry)			

Net Weight (kg): 330 Gross Weight (kg): 400
 Floor Space(W × L × H)(cm): 145 × 110 × 240 (including yarn creel)
 Packing Size(W × L × H)(cm): 95 × 110 × 180
 Air consumption per machine: 0.05~0.07m³ /MIN
 Air pressure per machine: 0.65MPa (6.5Kgf, 6.5Bar)
 Rated power per machine: 2.9~3.3KW (440V=6.6A~7.5A, 380V=7.63A~8.68A, 220V=13.2A~15A)
 Actual power per machine: 1.2~1.5KW (440V=2.72~3.41A, 380V=3.15~3.95A, 220V=5.45~6.81A)

★ Please visit our website for more information and updates.

REMARK

1. The maximum speed depends on various factors like yarns, stitch's types and lubrication etc.
2. Technical specification on this brochure is for the guidance purpose only. Susheng Machine(Jiaxing) Co.,Ltd. reserves all the right to amend and interpret the details of technical specifications on this brochure.